



POLY MAX HIGH TACK EXPRESS MOUNTING TAPE - WHITE

UNIVERSAL, EASY TO USE, EXTRA STRONG AND SUPER FAST WHITE



PRODUCT DESCRIPTION

Universal, easy to use, extra strong and super fast white double-sided mounting tape. Final strength: up to 150 KG per roll.

FIELD OF APPLICATION

Suitable for mounting of all kinds of smooth or slightly rough objects like fire detectors, coat hangers, (photo) frames, mirrors, small kitchen accessories, nameplates, house numbers, bathroom accessories etc. On numerous surfaces like metal, glass, tiles, rigid plastics, wood, stone, painted surfaces, etc. Not suitable for sensitive (e.g. wallpapers), non-stick coated surfaces (e.g. PTFE) and permanent humid places. Try on a small sample first.

PROPERTIES

- Extra strong
- Super fast
- In-/outdoor
- All materials
- Temperature resistant
- No drilling

PREPARATION

Working Conditions: Application temperature: +15°C to +30°C

Surface Requirements: Both parts must be firm, clean, dry and free of dust and grease.

APPLICATION

Directions for use:

1. Apply the mounting tape over the full length of the object to be mounted without removing the protective layer from the other side and press well for 10 sec. along the entire length of the tape (more pressure will give more bonding strength). 2. Remove the protective layer without touching the adhesive. 3. Position the object and press firmly for 10 sec. (more pressure gives more bonding strength). Final strength after approx. 24 hours.

Stains/residue: Remove tape residue with white spirit.

Points of attention: The adhesive strength depends on the quality of the surface and on the material and depth of the object; maximum adhesion is achieved with flat metal objects (depth <10 mm) on smooth and clean metal surfaces. 150KG per roll is tested according to Afera 5012, under ideal conditions (flat surfaces, temperature- and environmental conditions). May decrease over time.

TECHNICAL SPECIFICATIONS

Carrier type:	PE foam
Chemical base:	Synthetic rubber
Colour:	White
Holding power:	>168 hr (3,2kg)
Minimum application temperature:	15 °C
Maximum application temperature:	30 °C
Minimum temperature resistance:	-10 °C
Maximum temperature resistance:	75 °C
Peel adhesion:	10 N/25mm
Rolling ball tack:	24 cm
Thickness (mm):	0.98 mm

STORAGE CONDITIONS

Store well sealed, in a dry, cool and frost-free place

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.